

Juggernaut.Case™

Quick Disconnect Cable & Device Installation



1 remove Quick Disconnect Cable Assembly prior to inserting ****critical step****



2 open door latch to release door



3 insert device micro USB first to align home button with case button



4 securely close and latch door

micro USB can only be inserted in one direction

do not press on glass without device installed

only insert device in a clean dust-free environment

do not over tighten screws or use tools to tighten

refrain from opening door in dusty or wet conditions



5 inspect cable to ensure that the seal is clean and still attached



6 connect micro USB with cable facing toward the left side of the device/case



7 do not connect with the cable facing to the right



8 hold down middle of cable while tightening screws

Juggernaut.Case™
smartphones on the battlefield



Juggernaut.Case™ is a registered trademark of Juggernaut Defense, LLC
www.JuggernautCase.com
©2016, Rev. B, US Patents Pending

Juggernaut.Case™

Quick Disconnect Cable & Device Removal



- 1 start at the bottom of the case with the Quick Disconnect Cable/thumbscrews
- 2 loosen both screws until they disengage the case
- 3 pull Quick Disconnect Cable Assembly, by inboard screw, to disconnect from the device
- 4 inspect cable to ensure that the seal is clean and still attached

do not attempt to shake device out of the case

a pen or the eraser of a pencil are recommended

pull screws away from case body once loosened

pull screws away from case body once loosened

pull screws away from case body once loosened



- 5 open latch and door on top of the case
- 6 using a soft implement, gently push out the device
- 7 remove device from case
- 8 close door and re-latch to ensure dust and moisture do not enter case



Juggernaut.Case™ is a registered trademark of Juggernaut Defense, LLC
www.JuggernautCase.com
 ©2016, Rev. B, US Patents Pending